

Series 800 84-800 / 85-800 How To Order

SERIES

84 = 1.0A continuous (powers and controls 1 EExER device with signal output for 1 operator)

85 = 2.0A continuous (powers and controls EExER device for 1 pair of doors with signal output for 1 operator)

DELAYED EGRESS**

0 = 15 second delayed egress*
3 = 30 second delayed egress

ARMING OPTIONS

For standard 3 Chirps Arming, leave blank
SA = Silent Arming

REMOTE INDICATING UNIT COLOR

For standard Gray, leave blank
BLK = Black

CYLINDER

If cylinder not required or provided by others, leave blank (Dummy Plug Included)

MC65 = Mortise cylinder installed

IC7 = Interchangeable core housing installed

ALT BUILD

For standard build (powers 2 EExER devices), leave blank

ER = Powers (1) EExER and (1) ER exit device

EE = Powers (1) EExER and (1) EE exit device

REARM/RESET OPTIONS

For standard rearm/reset (using key or access control), leave blank

RKO = Rearm using key only

ARMING OPTIONS

0 = 15 second Arming*
1 = 1 second Arming
2 = xx second Arming

OUTPUT OPTIONS

For standard Door Signal Module (85-800), leave blank
M12 = 12VDC Module

SIGNAGE LANGUAGE

For standard English sign, leave blank

RFC = French/Canadian

RWS = Spanish

RWC = Chinese

MISCELLANEOUS

If not required, leave blank

KS = Key stop

SSK = Security screws for RIU

KSxSSK = Key stop and Security screws for RIU

RIU MOUNTING

For standard Surface Mounting, leave blank

F = Flush Mounting

NUISANCE

LN = Less Nuisance

*Indicates default

** Signage for delayed egress:

0 = ECL-395 included with rim

3 = ECL-395-1 included in p/s



Detex products can expose you to chemicals including Chromium (hexavalent compounds) and Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.detex.com/prop65